



BULLDOG® NEGATIVE AIR MACHINES

High CFM | Three Stages of Filtration | Easy Filter Removal

BD2KLV

BD2KLV

The BULLDOG 2KLV is the perfect portable for restoration, mold remediation and renovation contractors looking for high-performance HEPA filtration and exceptional durability at an economical price.

FEATURES & BENEFITS

- One-horsepower, two speed motor delivers airflow of 1950 on High and 600 on Low CFM
- BULLDOG® roto-molded body components are made from UL94HB flame retardant resin making it lightweight and virtually indestructible
- Four heavy-duty 4" casters (2 fixed and 2 locking swivel) provide mobility and maneuverability
- Standard filters include: 1 ea. polypad prefilter, 1 ea. pleated prefilter and 1 ea. 99.97% HEPA filter
Optional 12" HEPA and high-capacity carbon filters are available
- BD2KLV is equipped with a visual "change filter" indicator lamp
- The BD2KLV has been independently tested and certified in accordance with applicable UL and CSA safety requirements



TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	BD2KLV
Net Weight	lbs (kg)	117 (53.07)
Dimensions (L x W x H)	in (cm)	39.5 x 28.5 x 31.625 (100.33 x 72.39 x 80.33)
Electrical Rating	V, Hz, A	120 VAC, 60 Hz, 15 A
Airflow*, Max. w/ Clean Filters	CFM	1950 High Speed, 600 Low Speed
Normal Operating Amps Motor	A	9 or less 1 HP, 2 speed motor with thermal overload protection, auto reset, 60 Hz, single phase
Sound Level @ 5 Feet	dBA	70 on high speed
Cabinet Material	-	UL94HP flame retardant resin
Prefilter Access	-	Drop-in access door
First Stage Prefilter	1 ea	H2001, polypad
Second Stage Prefilter	1 ea	H2002, 2" deep particulate pleat
Alternate Second Stage	1 ea	VL2024, 2" deep high capacity carbon
HEPA Filter	1 ea	H242406-99, 6" deep 99.97% @ 0.3 microns
Alternate HEPA Filter	1 ea	H2010M, 12" deep 99.97% @ 0.3 microns

*Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.

Specifications and details are subject to change without prior notice.

CONTACT US FOR MORE INFORMATION



USA
1-800-634-9091
ABATEMENT.COM
IAQINFO@ABATEMENT.COM

CANADA
1-800-827-6443
ABATEMENT.CA
IAQINFO@ABATEMENT.CA

THE BD2KLV IS BEST SUITED FOR:



ABATEMENT & REMEDIATION



HEALTHCARE CONSTRUCTION