



# AQUATRAP® LGR DEHUMIDIFIER

Stackable | Efficient | Competitively Priced

AT250RS

## AT250RS

The AT250RS portable LGR dehumidifier from Abatement Technologies® is designed to make your structural drying work faster.

### FEATURES & BENEFITS

- Units may be stacked up to two high for space saving storage
- Folding handle is easily moved out of the way
- "No tools" filter changes
- Discharge hose equipped with quick connects on both ends
- Control panel is recessed for protection
- Handles are located on front and above wheels for easy lifting
- Soft-start compressor cycle reduces startup load
- Meets CSA / UL standards

### TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	AT250RS
Water Removal	-	(90° F/90% RH) 266 Pints/126L per day @ AHAM (80° F/60% RH) 147 Pints/70L per day
Operating temperature range	°F (°C)	34° - 100° (1.1° - 37.8°)
Refrigerant	-	R32
Max Power Consumption	W	1380 Watt
Voltage / Cycle	V / Hz	115V / 60Hz
Amperage	A	12 max
Rated Air Flow	-	413CFM / 700m <sup>3</sup> /h
Control Panel	-	Touchpad
Defrost Type	-	Sensor Controlled Thermodynamic Defrost
Air Filter	-	Pleated Filter (P/N: AT250FLTR)
Water Pump	-	Centrifugal
Housing	-	Rotomolded Plastic
Drain Hose Length	ft (m)	32 (10)
Cord Length	ft (m)	25 (7.6)
Dimensions (LxWxH)	in (cm)	19.6 x 19.6 x 33.5 (50 x 50 x 85)
Weight	lb (kg)	100 (45.5)

Specifications and details are subject to change without prior notice.



XACTIMATE CODE: WTR-DHM>>  
XACTIMATE PRODUCT CATEGORY: LGR

### CONTACT US FOR MORE INFORMATION



USA  
1-800-634-9091  
ABATEMENT.COM  
IAQINFO@ABATEMENT.COM

CANADA  
1-800-827-6443  
ABATEMENT.CA  
IAQINFO@ABATEMENT.CA

### THE AT250RS IS BEST SUITED FOR:

- DISASTER RESTORATION
- ABATEMENT & REMEDIATION
- HEALTHCARE CONSTRUCTION
- HEALTHCARE FACILITIES