



# HEPA-AIRE® PORTABLE AIR SCRUBBER

## Lightweight | Compact | Portable

PAS1200

### PAS1200

The compact, upright design of the lightweight PAS1200UV model enables it to fit easily into very small spaces inaccessible to negative air machines or other larger units.

### FEATURES & BENEFITS

- Variable speed airflow, with maximum rated airflow as high as 900 CFM
- Anodized aluminum cabinet is lightweight, corrosion, and scratch resistant
- Power consumption of less than 3.5 amps @ 120VAC allows for daisy-chaining multiple units per 15A circuit
- Upright design includes a built-in transport dolly, non-marking rear wheels and front 360° swivel casters
- Offset rear wheels make it easy to move up or down stairs
- Hinged, "no tools" prefilter access
- Recessed and sealed control panel
- The PAS1200UV has been independently tested and certified in accordance with applicable UL and CSA safety requirements

### TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	PAS1200
Net Weight	lbs (kg)	85 (38.56)
Dimensions (L x W x H)	in (cm)	19.75 x 22 x 39 (7.775 x 8.66 x 15.35)
Electrical Rating	V, Hz, A	120 VAC, 60 Hz, 15 A
Airflow*, Max. w/ Clean Filters	CFM	900 on High, 300 on Low
Normal Operating Amps	A	3.5 or less
Motorized Impeller	-	400 watt, auto reset, 60 Hz, single phase
Sound Level @ 5 Feet	dBA	62-67 on high speed
HEPA Filter Efficiency	-	99.97% @ 0.3 microns
Cabinet Material	-	20 gauge stainless steel
Prefilter Access	-	Hinged "no tools" access door
First Stage Prefilter	1 ea	F621, 1" deep coarse particulate
Second Stage Prefilter	1 ea	H502, 2" deep pleated particulate
Optional Second or Third Stage	1 ea	VL1002, 2" deep high capacity carbon
HEPA Filter	1 ea	H610C-99

Specifications and details are subject to change without prior notice.



\*Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.

### CONTACT US FOR MORE INFORMATION



#### USA

1-800-634-9091  
ABATEMENT.COM

IAQINFO@ABATEMENT.COM

#### CANADA

1-800-827-6443  
ABATEMENT.CA

IAQINFO@ABATEMENT.CA

### THE PAS1200 IS BEST SUITED FOR:



HEALTHCARE CONSTRUCTION



ABATEMENT & REMEDIATION



HEALTHCARE FACILITIES



CRITICAL ENVIRONMENT PROTECTION