



PREDATOR® PORTABLE AIR SCRUBBER

Lightweight | Portable | Stack for Storage and Transport

PRED750

PRED750

With next-generation technology, the PRED750 features a unique, updated double-wall polymer cabinet and design that produces exceptional airflow and durability to make your jobs easier and more profitable.

FEATURES & BENEFITS

- Variable speed airflow, with maximum rated airflow as high as 750 CFM
- Ultra-compact, light weight cabinetry, integral ergonomic lift handle and perfect weight balance
- Stackable for easy storage and transport - can stack 3 high for usage and up to 5 units high for transportation or storage
- Rotomolded body components are made from UL94HB flame retardant resin
- Safely daisy-chain up to five units on one 15 amp circuit
- "Zero Bypass" cabinet design
- Easy access for fast pre-filter and HEPA filter replacement
- Custom colors available (minimum quantities apply)
- The PRED750 has been independently tested and certified in accordance with applicable UL and CSA safety requirements

TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	PRED750
Net Weight	lbs (kg)	35 (15.88)
Dimensions (L x W x H)	in (cm)	25.5 x 19.5 x 20.5 (64.77 x 49.53 x 52.07)
Electrical Rating	V, Hz, A	110-120 VAC, 60 Hz, 15 A
Airflow*, Max. w/ Clean Filters	CFM	750 on High, 200 on Low
Normal Operating Amps	A	1.9 or less
Motorized Impeller	-	258 watt, auto reset, 60 Hz, single phase
Sound Level @ 5 Feet	dBA	65 on high speed
HEPA Filter Efficiency	-	99.97% @ 0.3 microns
Cabinet Material	-	Polyethylene Cabinet Made From UL94HB Flame Retardant Resin
Pre-filter Access	-	Hinged "no tools" access door
First Stage Pre-filter	1 ea	F621, 1" deep coarse particulate
Second Stage Pre-filter	1 ea	H502, 2" deep pleated particulate
Optional Second Stage	1 ea	VL1002, 2" deep high capacity carbon
HEPA Filter	1 ea	H161606-99

Specifications and details are subject to change without prior notice.



US Patent No. 9,868,082 / Utility
 US Patent No. D742495 / Design
 Canadian Patent No. 156184 / Design
 Canadian Patent No. 2,852,880 / Utility

*Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.

CONTACT US FOR MORE INFORMATION



USA
 1-800-634-9091
 ABATEMENT.COM
 IAQINFO@ABATEMENT.COM

CANADA
 1-800-827-6443
 ABATEMENT.CA
 IAQINFO@ABATEMENT.CA

THE PRED750 IS BEST SUITED FOR:

- HEALTHCARE CONSTRUCTION
- CRITICAL ENVIRONMENT PROTECTION
- ABATEMENT & REMEDIATION
- HEALTHCARE FACILITIES